

LED IP65 Triproof light TPC(PRO)





| Input Voltage | Rated Power | Chips | Driver | CCT | CRI | Beam Angle |
|---------------|------------------------|----------|--------------------------|----------------------------------|--------------|----------------------------|
| AC220-240V | 1.2m 40W/ 1.5m 60W | Samsung | Hahga | 4000K/3000K | 80 | 120° (other for customize) |
| Efficiency | Housing Material | Finished | Box Qty | Box Size | G.Weight | |
| 130lm/W | Alu housing + PC cover | Grey | 1.2m: 9pcs 1.5m: 9pcs | 1310*270*310mm 1610*270*310mm | 12kg 15kg | |

- ▶ Built with a tough, air-tight enclosure allowing it to resist jets of water and dust an essential feature for outdoor lighting & Industry lighting.
- ▶ Low consumption; More than 80% saving of the power
- ► Low light decay, Long lifetime 50,000Hours
- ► Water-proof, Dust-proof, Damp-proof, Vapor-proof, IP66
- ► High impact test, IK10
- ▶ Self-wiring connection/ Linkable.
- ▶ Easy to install
- ▶ SMD LED Type the lifetime is 50,000 hours
- ▶ 6063 aluminum extrusion with good heat-dissipation
- ► CRI:>80, IP66 protection class
- ▶ High Quality Hahga Driver / Osram Driver
- ► AC Input: 220V-240V,50/60Hz
- ► No Flickering, 5 Wires 3 phase Series Linkable

| EAN. | Model No. | Wire | Power | CCT | Lumen Output |
|----------|------------|---------|----------|-------|--------------|
| 69013195 | 3201824608 | 5 wires | 1.2m 40W | 4000K | 5200lm |
| 69013201 | 3201825608 | 5 wires | 1.5m 60W | 4000K | 7800lm |





















